





Approved for use in Miami-Dade HVHZ Zones Florida Building Code Approved Product Approval FL 17838

www.euro-wall.com 888.989.EURO (3876)



SYSTEM THRESHOLDS

Maximum / Minimum Specifications

Max Panel Weight: 350 lbs each panel

Max Panel Height: 168"
Max Panel Width: 52"
Min Panel Height: 32"
Min Panel Width: 18"

Panel Thickness:

usage and limitation

NOTE: When using maximum panel widths & heights, panels may exceed maximum panel weight of 350 lbs. Calculated weight check should be done. For installations in Florida, please see the Florida Product Approval for usage and limitations.

SYSTEM HIGHLIGHTS

Extrusions

Extruded aluminum 6063-T5 with door panel corner keys for strength and security

2-1/4"

Hardware

Stainless steel (316/304SS) components with aluminum hinges

Twinpoint Hardware

Stainless steel (304SS) and aluminum components

Lever Lock Sets

3 hooks + top and bottom shootbolts 5 point locking system

Multipoint Door Locks

Faceplate, latch and hooks are stainless steel 304SS

Sills

Standard, modified standard and ADA options (all impact rated - standard sill water rated)

Matching Fixed Units

Matching Florida Product Approved impact rated transom and sidelight units available

Configuration

Straight, segmented, radius and split height configurations (all impact tested / Florida Product Approved)

Corner Units

90° postless corner units (impact tested / Florida Product Approved)

Largest Panel Sizes

14' tall and up to 52" wide panels - the largest available Florida Product Approved folding door panels

Long Lasting Finish

Standard finish coating is AAMA 2605, the highest quality finish available

Compliant

ADA sill that is HVHZ impact tested

Under Pressure


Up to 100+/- DP impact tested

Aesthetics


Custom muntins, simulated divided lites, mid-rails, kick plates, custom colors, interior wood cladding and faux wood grain finishes available




SYSTEM COMPONENTS



SILL OPTIONS





PANEL FINISH OPTIONS

STANDARD FRAME & DOOR PANEL FINISHES





Class I



AAMA 2605



Black AAMA 2605

STANDARD FRAME & DOOR PANEL FINISHES

- Powder coat or Kynar® finishes available
- Custom powder coat or Kynar[®] finishes available
- · Manufacturer color match options
- · Custom faux wood grain finishes available

INTERIOR WOOD CLAD FINISH OPTION

- · Mahogany / sapele
- · White oak
- Additional wood species available



HARDWARE / HANDLE FINISH OPTIONS

MULTIPOINT LOCK HANDLE

TWINPOINT LEVER

HINGES / HARDWARE





Available Finishes

Polished Stainless Steel
Brushed Satin
Bronze
Black

Available Finishes

White
Brushed Satin
Bronze
Black
Custom Colors Available


Available Finishes
White
Brushed Satin

Bronze Black


NOTE: The colors shown are an approximation of actual color and finish. Actual colors and finishes



FOLDING CONFIGURATIONS




*Daily access doors available for egress.



Twinpoint assembly is used in securing each pair of folding door panels in the closed position.

NOTE: The configurations on this page are just a few examples of the numerous possibilities for Euro Vista Fold™ Door layout options.

SPECIALTY CONFIGURATION




3L4R 7R






PANEL CROSS SECTION

Outswing Extrusion Shown






GLAZING DETAILS

Available impact glass options for the Euro Vista Fold™:


Aluminum Pivot Door

- IG Impact
- 9/16" Impact Monolithic

9/16" Monolithic Glass • Impact Rated



1" Insulated Glass • Impact Rated



TEST PERFORMANCES

- Approved for use in Miami-Dade HVHZ Zone
- Florida Building Code Approved Product Approval FL 17838
- TAS 201 TAS 202 TAS 203
- —□ Tested for Thermal Requirements
- —— AAMA / WDMA / CSA 101 / I.S.2 / A440-08 NAFS-08

- —□ Air Infiltration: A2
- Water Leakage Resistance: DP75 or PG75
- —□ Wind Load Resistance: up to DP100
- Wind Zone 4 (Hurricane) ASTM (cycling) E1996: DP100 (C3 H100 Series)
- Wind Zone 4 (Hurricane) ASTM (impact) E1886: Pass (C3 H100 Series)

DESIGN PRESSURE CHART


Wind Zone 3 Width & Height Design Pressure Chart Panel Width (Inches)

		20	24	28	32	36	40	44	48	52
Panel Height (Inches)	96	100	100.0	100.0	100.0	100.0	75	65	65	65
	102	100	100.0	100.0	98.8	88.6	75	65	65	
	108	100	100.0	93.8	82.8	75	65	65		
	114	100	92.2	79.5	75	75	65	+61.2/-65		
	120	94.2	78.9	75	75	+64.6/-65	+58.6/-63.5			
	126	81.3	75	74.4	65.5	+55.6/-60.2	+50.4/-54.6			
	132	75	75	64.6	+53.9/-58.4	+48.2/-52.2				
	138	75	65.6	56.5	+47.1/-51	+42.1/-45.6				
	144	69	57.7	49.6	+41.4/-51					
	150	61	51	43.8	+36.5/-39.6					
	156	54.2	45.3	+36.9/-40	+32.4/-35.1					
	162	48.3	40.4	+32.9/-35.7						
	168	43.3	36.2	+29.5/-32						

HVHZ Width & Height Design Pressure Chart Panel Width (Inches)

		20	24	28	32	36	40	44	48	52
Panel Height (Inches)	72	100	100	100	100	100	100	100	100	75
	76	100	100	100	100	100	100	100	100	75
	80	100	100	100	100	100	100	100	75	75
	84	100	100	100	100	100	100	100	75	65
	88	100	100	100	100	100	100	75	65	65
	92	100	100	100	100	100	100	75	65	65
	96	100	100	100	100	100	75	65	65	65
	100	100	100	100	100	94.3	75	65	65	
	104	100	100	100	92.9	75	75	65	+64.5/-65	
	108	100	100	93.8	82.8	75	65	65		
	112	100	97.3	83.9	75	75	65	+62.6/-65		
	116	100	87.4	75.4	75	75	+64.5/-65			
	120	94.2	78.9	75	75	+64.6/-65	+58.6/-63.5			
	126	65	65	65	65	65	65			
	132	65	65	65	65	65				
	138	65	65	65	65	65				
	144	65	65	65	65	65				

Note: Applies to both inswing and outswing configurations, segmented and radius installations



EURO-WALL 10 YEAR WARRANTY

Euro-Wall warrants the products to be free from manufacturing defects for a period of 10 years from the date of purchase.

888.989.EURO (3876) W W W . e u r o - w a l l . c o m

MANUFACTURING

2200 Murphy Court North Port, Florida 34289 888.989.3876 • 941.979.5316

euro-wall

FOLDING | SLIDING | STACKING | PIVOT

SHOWROOM

1211 Stirling Road, Unit 102, Dania Beach, Florida 33004 954.610.2572

Proud Member of the American Architectural Manufacturers Association.

